

ESTD. SINCE 1954



DOUBLE ACTING HOLLOW PLUNGER HYDRAULIC CYLINDERS

Technical Parameters

| Model | Tonnage (T) | Stroke (mm) | Closed Height A(mm) | Extended Height B(mm) | Outside Dia D(mm) | Centre Hole G(mm) | Inside Dia E(mm) | Piston Dia F(mm) | G.W. (kg) |
|---------------|-------------|-------------|---------------------|-----------------------|-------------------|-------------------|------------------|------------------|-----------|
| HHYG-6050KS | 60 | 50 | 402 | 230 | 158 | 54 | 123 | 90 | 24.5 |
| HHYG-60100KS | | 100 | 803 | 330 | | | | | 31.3 |
| HHYG-10050KS | 100 | 50 | 689 | 238 | 212 | 80 | 166 | 130 | 44.7 |
| HHYG-100100KS | | 100 | 1379 | 338 | | | | | 56.6 |
| HHYG-15050KS | 150 | 50 | 1118 | 250 | 258 | 100 | 210 | 170 | 69.7 |
| HHYG-150100KS | | 100 | 2236 | 350 | | | | | 87.2 |
| HHYG-20050KS | 200 | 50 | 1436 | 265 | 288 | 120 | 240 | 190 | 90.9 |
| HHYG-200100KS | | 100 | 2873 | 365 | | | | | 112.0 |

*Manufacturing Tolerance will be $\pm 10\text{MM}$

ORIENTAL TRADING CORPORATION
ISO : 9001-2008 Co

Reg. Office : 33/1, N.S Road, Marshall House,
Ground Floor, Room No. 37, Kolkata - 700 001.
Phone No. : +91-33-2230 9759, 2230 9557, 4005 5077.
Email : otccal@gmail.com