

ESTD. SINCE 1954

Single Acting Hydraulic Cylinders (Jack) Plain Ram

Technical Parameters

Model	Tonnage (T)	Stroke (mm)	Closed Height A(mm)	Extended Height B(mm)	Outside Dia (mm)	Inside Dia (mm)	Piston Dia(mm)	G.W. (kg)
HHYG-1050	10	50	122	172	68	45	36	3.1
HHYG-10100		100	172	272				4.4
HHYG-10150		150	222	372				5.7
HHYG-2050	20	50	126	176	78	60	45	4
HHYG-20100		100	176	276				5.3
HHYG-20150		150	226	376				6.6
HHYG-3050	30	50	137	187	103	75	65	7.9
HHYG-30100		100	187	287				10.7
HHYG-30150		150	237	387				13.5
HHYG-5050	50	50	147	197	123	95	70	11.6
HHYG-50100		100	197	297				14.9
HHYG-50150		150	247	397				18
HHYG-10050	100	50	182	232	168	135	90	25.7
HHYG-100100		100	232	332				30.6
HHYG-100150		150	282	432				35.5
HHYG-15050	150	50	182	232	205	165	115	43
HHYG-150100		100	232	332				53
HHYG-150150		150	282	432				63
HHYG-20050	200	50	202	252	228	190	135	60
HHYG-200100		100	252	352				71
HHYG-200150		150	302	452				83
HHYG-25050	250	50	248	298	270	215	180	105
HHYG-250150		150	348	498				142
HHYG-250300		300	498	798				196
HHYG-30050	300	50	267	317	285	240	200	126
HHYG-300150		150	367	517				165
HHYG-300300		300	517	817				224
HHYG-40050	400	50	315	365	325	270	220	195
HHYG-400150		150	415	565				245
HHYG-400300		300	565	865				318
HHYG-50050	500	50	345	395	373	305	250	283
HHYG-500150		150	445	595				349
HHYG-500300		300	595	895				451
HHYG-60050	600	50	371	421	402	330	270	354
HHYG-600150		150	471	621				431
HHYG-600300		300	621	921				546
HHYG-80050	800	50	424	474	472	390	320	560
HHYG-800150		150	524	674				665
HHYG-800300		300	674	974				825
HHYG-100050	1000	50	477	527	530	430	360	799
HHYG-1000150		150	577	727				937
HHYG-1000300		300	727	1027				1145

*Manufacturing Tolerance will be $\pm 10\text{MM}$

ORIENTAL TRADING CORPORATION

ISO : 9001-2008 Co

Reg. Office : 33/1, N.S Road, Marshall House,
Ground Floor, Room No. 37, Kolkata - 700 001.

Phone No. : +91-33-2230 9759, 2230 9557, 4005 5077.

Email : otccal@gmail.com

ESTD. SINCE 1954



Single Acting Hydraulic Cylinders (Jack) Plain Ram

Technical Parameters

Model	Tonnage(T)	Closed Height (mm)	Power Lift in (mm)	Extended Height B(mm)	RAM Dia in (mm)	Outside Cylinder Dia in (mm)	Net Weight in kgs Approx.	Type of Pump
RHD-10150	10	220	150	370	45	70	6	ONE
RHD-20150	20	225	150	375	60	85	7	ONE
RHD-30150	30	240	150	390	75	105	14	ONE
RHD-50150	50	265	150	415	95	150	32	TWO
RHD-100150	100	285	150	435	145	215	69	TWO
RHD-150150	150	300	150	450	180	265	115	TWO
RHD-200150	200	310	150	460	200	310	165	TWO
RHD-300150	300	315	150	465	255	380	260	TWO
RHD-400150	400	355	150	505	290	420	345	TWO
RHD-500150	500	410	150	560	343	480	525	TWO
RHD-750150	750	475	150	625	425	590	990	POWER
RHD-1000150	1000	495	150	645	510	680	1300	POWER

*Manufacturing Tolerance will be $\pm 10\text{MM}$

ORIENTAL TRADING CORPORATION
ISO : 9001-2008 Co

Reg. Office : 33/1, N.S Road, Marshall House,
Ground Floor, Room No. 37, Kolkata - 700 001.
Phone No. : +91-33-2230 9759, 2230 9557, 4005 5077.
Email : otccal@gmail.com