

ESTD. SINCE 1954



ALUMINIUM HYDRAULIC CYLINDER

Technical Parameters

Model	Tonnage (T)	Stroke (mm)	Closed Height A(mm)	Extended Height B(mm)	Outside Dia (mm)	Inside Dia (mm)	Piston Dia(mm)	G.W. (kg)
HHYG-1050L	10	50	142	192	60	45	38	1.2
HHYG-10100L		100	192	292				1.7
HHYG-10150L		150	242	392				2.1
HHYG-2050L	20	50	162	212	85	60	52	3
HHYG-20100L		100	212	312				3.8
HHYG-20150L		150	262	412				4.6
HHYG-3050L	30	50	172	222	110	75	62	5.1
HHYG-30100L		100	222	322				6.4
HHYG-30150L		150	272	422				7.6
HHYG-5050L	50	50	182	232	140	95	80	8.6
HHYG-50100L		100	232	332				10.5
HHYG-50150L		150	282	432				12.5
HHYG-10050L	100	50	208	258	180	135	110	17
HHYG-100100L		100	258	358				20.5
HHYG-100150L		150	308	458				23.3
HHYG-15050L	150	50	233	283	230	165	135	30.9
HHYG-150100L		100	283	383				35.9
HHYG-150150L		150	333	483				40.9
HHYG-20050L	200	50	263	313	270	190	160	47.5
HHYG-200100L		100	313	413				51.6
HHYG-200150L		150	363	513				61.2
HHYG-200200L		200	413	613				68.0
HHYG-200250L		250	463	713				74.8

*Manufacturing Tolerance will be $\pm 10\text{MM}$

ORIENTAL TRADING CORPORATION
ISO : 9001-2008 Co

Reg. Office : 33/1, N.S Road, Marshall House,
 Ground Floor, Room No. 37, Kolkata - 700 001.
 Phone No. : +91-33-2230 9759, 2230 9557, 4005 5077.

Email : otccal@gmail.com